

1300

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

· Watertight, crushproof, and dustproof

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck[™] with convoluted lid foam
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1300 Standard



1300NF No Foam



1300WF With Foam

DIMENSIONS

 Interior (L×W×D)
 9.17 x 7.00" x 6.12 (23.3 x 17.8 x 15.5 cm)

 Exterior (L×W×D)
 10.62 x 9.68" x 6.87 (27 x 24.6 x 17.4 cm)

 Lid Depth
 1.18" (3 cm)

 Bottom Depth
 4.93" (12.5 cm)

 Total Depth
 6.11" (15.5 cm)

 Int Volume
 0.23 ft³ (0.007 m³)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS

Black Orange Silver Yellow

WEIGHT

 Weight With Foam
 3.53 lbs (1.6 kg)

 Weight Empty
 3.09 lbs (1.4 kg)

 Buoyancy
 12.35 lbs (5.6 kg)

 Master Pack Weight
 16.85 lbs (7.6 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Master Pack 4 Military yes

ACCESSORIES



1203 Replacement O-ring



1301 4 pc. Replacement Foam Set



1200PFSpecial Application Panel Frame



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel