



0350

Protector

Cube Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Large 2-person fold down handles**
- **Watertight, crushproof, and dustproof**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



0350
Standard



0354
With Padded Dividers



0350NF
No Foam



0350WF
With Foam

DIMENSIONS

Interior (LxWxD)	20.00 x 20.00" x 20.00 (50.8 x 50.8 x 50.8 cm)
Exterior (LxWxD)	22.50 x 22.43" x 21.25 (57.2 x 57 x 54 cm)
Lid Depth	5.00" (12.7 cm)
Bottom Depth	15.00" (38.1 cm)
Total Depth	20" (50.8 cm)
Int Volume	4.63 ft ³ (0.131 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer

Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

WEIGHT

Weight With Foam	32.01 lbs (14.52 kg)
Weight Empty	25.99 lbs (11.79 kg)
Buoyancy	268.96 lbs (122 kg)
Master Pack Weight	33.89 lbs (15.37 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

CERTIFICATIONS

IP67
Def Stan 81-41

OTHER

Master Pack	1
Nameplate	yes
Reduced Area	yes
Military	yes

ACCESSORIES



0351
7 pc. Replacement Foam Set



0353
Replacement O-ring



0355
Padded Divider Set



0357
Cube Case Mobility Package



1507QM
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 04-28-26