

## 9415Z0

#### 9410L + SAFETY = 9415Z0

# Everything that's great about the 9410L LED Lantern, plus safety certificates

At just 1.4kg (3 pounds) and 530 lumens, the 9415Z0 LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 272 meters. And it's loaded with innovative technology and features you have come to expect from Peli.

Safety certified for the most volatile work areas, the 9415Z0 LED Lantern is safe and one of the most compact, high output lanterns on the market. Certified to ATEX Zone 0 (Category 1)



#### **DIMENSIONS**

**Length** 8.75" (22.2 cm)

#### **MATERIALS**

**Body** Anti-static Impact Modified PC/PBT

**O-Ring** EPDM

LensAnti-static coated Polycarbonate (PC)ShroudAnti-static Impact Modified PC/PBT

## **COLOURS**

High Visibility Yellow

### LIGHT SPECS

Lamp Type LED

#### **POWER**

Battery Size C
Battery Type NiMH
Battery Quantity 4
Batteries Included yes
Rechargeable yes
Charge Time 15 hrs
Battery Level Indicator RGB LED
Volts 4.8v

## WEIGHT

Weight With Batteries 58.2 oz (1650 gr)

## **SWITCH**

**Switch Type** Push Button

## **CERTIFICATIONS**

ATEX Zone 0 **IECEx** ia

## OTHER

**Minimum Pack** Package Code

1

В

| FL1 STANDARD | HIGH          | LOW           |
|--------------|---------------|---------------|
| 314          | 530<br>LUMENS | 202<br>LUMENS |
| $\odot$      | 4h 30mins     | 11h 30mins    |
|              | 272m          | 166m          |
|              | 18480cd       | 6914cd        |
|              | IPX4          |               |

## **ACCESSORIES**



**9416 8056F**Deck/Dash Charger Base Unit 12v Plug-in for Fast Charger





9418Z0 Replacement Battery



**6061F** Direct Wiring Rig for Fast Charger



6058H 220V Transformer (UK)

Document created on 10-18-25