

# 1470

## **Protector**

Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

### Double safety locking latches with keys

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck<sup>™</sup> with convoluted lid foam
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



### **CONFIGURATIONS**







1470NF No Foam



1470WF With Foam

#### **DIMENSIONS**

Interior (L×W×D) 15.70 x 10.70" x 3.87 (39.9 x 27.2 x 9.8 cm) Exterior (L×W×D) 16.88 x 13.23" x 4.47 (42.9 x 33.6 x 11.4 cm)

 Lid Depth
 1.47" (3.7 cm)

 Bottom Depth
 2.40" (6.1 cm)

 Total Depth
 3.87" (9.8 cm)

 Int Volume
 0.38 ft³ (0.011 m³)

 Padlock Hole Diameter
 0.25" (0.6 cm)

## **MATERIALS**

Body ABS
Latch ABS
O-Ring Polymer
Pins Stainless Steel
Foam 1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

### **COLOURS**

### Black

### WEIGHT

 Weight With Foam
 5.51 lbs (2.5 kg)

 Weight Empty
 4.28 lbs (1.9 kg)

 Buoyancy
 24.91 lbs (11.3 kg)

 Master Pack Weight
 22.20 lbs (10.1 kg)

### **TEMPERATURE**

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 190°F (87.8 °C)

### **CERTIFICATIONS**

### MIL C-4150J

### **OTHER**

Master Pack4NameplateyesMilitaryyes

### **ACCESSORIES**



**1471** 3 pc. Replacement Foam Set



**1472** Shoulder Strap



**1473** Replacement O-ring



**1470PF**Special Application Panel Frame



**1507** Quick Mounts - set of 4



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel