



1495 Protector Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **3 dial combination lock included**
- **Fits up to 17" laptops**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down over-molded handle
- Padded shoulder strap
- Pick N Pluck™ with convoluted lid foam
- Stainless steel padlock protectors
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1495
Standard



1495NF
No Foam



1495WF
With Foam

DIMENSIONS

Interior (L×W×D)	18.87 x 13.12" x 3.81 (47.9 x 33.3 x 9.7 cm)
Exterior (L×W×D)	21.62 x 17.25" x 4.87 (54.9 x 43.8 x 12.4 cm)
Lid Depth	1.12" (2.8 cm)
Bottom Depth	2.68" (6.8 cm)
Total Depth	3.8" (9.7 cm)
Int Volume	0.55 ft ³ (0.016 m ³)
Padlock Hole Diameter	0.25" (0.6 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel

Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

 Black  Desert Tan

WEIGHT

Weight With Foam	8.37 lbs (3.8 kg)
Weight Empty	7.23 lbs (3.28 kg)
Buoyancy	45.15 lbs (20.48 kg)
Master Pack Weight	23.00 lbs (10.43 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

CERTIFICATIONS

IP67
Def Stan 81-41

OTHER

Master Pack	2
Nameplate	yes

ACCESSORIES



1472
Shoulder Strap



1481
3 pc. Replacement Foam Set



1483
Replacement O-ring



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

