



472-PWC-M16-3200

Mobile Armory™

Rifle Case

- Six Press & Pull Latches
- Two Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- In-line Wheels
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX™ Resin
- Watertight
- Peli's limited lifetime guarantee*
- *Where applicable by law



DIMENSIONS

| | |
|-------------------------|--|
| Interior (LxWxD) | 44.00 x 14.00" x 6.00 (111.8 x 35.6 x 15.2 cm) |
| Exterior (LxWxD) | 47.20 x 16.50" x 6.70 (119.9 x 41.9 x 17 cm) |
| Lid Depth | 2.00" (5.1 cm) |
| Bottom Depth | 4.00" (10.2 cm) |
| Total Depth | 6" (15.2 cm) |
| Int Volume | 2.14 ft ³ (0.061 m ³) |

MATERIALS

| | |
|-------------------------|--|
| Body | Injection Molded HPX™ high performance resin |
| Latch | Valox - Polybutylene Terephthalate (PBT) |
| Latch (Alt) | Xenoy - Polyester/Polycarbonate blend |
| O-Ring | Silicone Sponge |
| Pins | Stainless Steel |
| Foam | 1.3/1.35 polyester |
| Purge Body | Valox - Polybutylene Terephthalate (PBT) |
| Purge Body (Alt) | Xenoy - Polyester/Polycarbonate blend |
| Purge Vent | Gortex membrane |

COLOURS

| | |
|---|--|
|  Black |  OD Green |
|---|--|

WEIGHT

| | |
|---------------|---------------------|
| Weight | 21.10 lbs (9.57 kg) |
|---------------|---------------------|

TEMPERATURE

| | |
|----------------------------|------------------|
| Minimum Temperature | -20°F (-28.9 °C) |
| Maximum Temperature | 140°F (60 °C) |

OTHER

| | |
|---------------|---|
| Wheels | 2 |
|---------------|---|

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 05-03-26