



# DE2410-02-35-05

## Classic Rack

3U

Peli™ Classic Rack cases are ideal for rack mountable precision test, electro-mechanical, medical and biological diagnostic equipment, memory storage devices, meteorological instruments, mobile operations, broadcast and video gear, laboratory equipment, aerospace instrumentation, servers, military mission planning, command and control equipment, and flight simulators.

- The best shock and vibration protection available
- Protection for equipment from 20-340 lbs
- Equipment typically will have 15-30 G fragility



### DIMENSIONS

|                                |   |
|--------------------------------|---|
| <b>Exterior (LxWxD)</b>        | 45.80 x 27.00" x 12.30 (116.3 x 68.6 x 31.2 cm) |
| <b>Rack Depth</b>              | 33.00" (83.8 cm)                                |
| <b>Interior Lid Depth</b>      | 2.50" (6.4 cm)                                  |
| <b>Interior Back Lid Depth</b> | 5.25" (13.3 cm)                                 |

### MATERIALS

### COLOURS

|                                 |                                     |                                |                                |
|---------------------------------|-------------------------------------|--------------------------------|--------------------------------|
| ■ Black - 032 Fed Std<br>27040  | ■ Olive Drab - 137 Fed<br>Std 34096 | ■ Tan - 250 Fed Std<br>20372   | ■ Red - 130 Fed Std<br>21105   |
| ■ Blue - 135 Pantone<br>292U    | ■ White - 132 Fed Std<br>27925      | ■ Yellow - 136 Pantone<br>012U | ■ Green - 138 Fed Std<br>24052 |
| ■ Orange - 134 Fed Std<br>12197 | ■ Yellow - 131 Fed Std<br>23538     | ■ Maroon - 197 Pantone<br>202U | ■ Blue - 101 Fed Std<br>25052  |
| ■ Purple - 129 Pantone<br>245U  |                                     |                                |                                |

### WEIGHT

|               |                     |
|---------------|---------------------|
| <b>Weight</b> | 51.00 lbs (23.1 kg) |
|---------------|---------------------|

#### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 04-04-25