



PR2012-01/18/01

ProRack™
6U

Peli™ ProRack™ cases are lightweight, space-efficient, front and rear opening transport container (not a shock mounted/cushioned rackmount system) for field ruggedized equipment.

- Designed for equipment up to 75 lbs
- Equipment typically will have 80-120 G fragility
- Rugged 18" deep cases w/ aircraft aluminum frame suspended on plastic fins to protect your gear from direct impact transmission
- Often used for field-deployed amplifiers and electronic, medical or testing equipment components



DIMENSIONS

| | |
|--------------------------------|--|
| Exterior (L×W×D) | 22.00 x 22.40" x 14.80 (55.9 x 56.9 x 37.6 cm) |
| Rack Depth | 18.00" (45.7 cm) |
| Interior Lid Depth | 1.81" (4.6 cm) |
| Interior Back Lid Depth | 1.81" (4.6 cm) |

MATERIALS

COLOURS

■ Black - 032 Fed Std
27040

WEIGHT

| | |
|---------------|---------------------|
| Weight | 23.90 lbs (10.8 kg) |
|---------------|---------------------|

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 07-24-25