



2315Z0

The hazard horizon is bright. With ATEX Zone 0 (Category 1) Safety Certification, 115 lumens, 75 meters of spot beam distance and an IPX8 Waterproof rating, the Peli™ 2315Z0 flashlight stretches light across dark, hazardous environments without being a source of ignition.

Engineered with an aluminum core and ABS overmoulded plastic, this flashlight is built for rough handling and can survive hard drops. Plus, the sturdy clip attaches to a work vest for fast access and the tail switch activates raw LED power, even when using heavy-duty work gloves.

Peli™ 2315Z0 - SEE THE LIGHT AT THE END OF THE TUNNEL

- Built Peli tough
- 2 AA Batteries (included)
- ATEX Safety Certified Zone 0 (Cat. 1)
- Integrated Clip
- Full / Momentary Activation Tail Switch
- IPX8 1m waterproof
- Helmet mount (included)



DIMENSIONS

| | |
|---------------|-----------------|
| Length | 6.22" (15.8 cm) |
|---------------|-----------------|

MATERIALS

| | |
|---------------|-----|
| Body | ABS |
| O-Ring | NBR |
| Lens | PC |
| Shroud | ABS |
| Clip | ABS |

COLOURS

| |
|--|
|  High Visibility Yellow |
|--|

LIGHT SPECS

| | |
|------------------|-----|
| Lamp Type | LED |
|------------------|-----|

POWER

| | |
|---------------------------|----------|
| Battery Size | AA |
| Battery Type | Alkaline |
| Battery Quantity | 2 |
| Batteries Included | yes |
| Volts | 3.0v |

WEIGHT






| | |
|---------------------------------|-----------------|
| Weight With Batteries | 4.6 oz (130 gr) |
| Weight Without Batteries | 2.8 oz (79 gr) |

SWITCH

Switch Type Momentary Push Button
Light Modes High

CERTIFICATIONS

IECEX ia
ATEX Zone 0

| FL1 STANDARD | HIGH |
|---|---------------|
|  | 115 LUMENS |
|  | 6h 0mins |
|  | 75m |
|  | 1403cd |
|  | IPX8 (1m) |

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 08-16-24