

# 1506 <sub>Air</sub>

Peli understands that finding the right protection, with the perfect fit for your gear, is a priority. Peli<sup>™</sup> Air began with long protection and quickly grew to offer you deep protection. The time has come to combine those two in order to create Peli's new Long/Deep Series. Gone are the days of dangerously forcing your equipment into the wrong size case or leaving it unprotected with no other options. With Peli's Long/Deep series, we've created the missing link so that no matter the demands of your gear, Peli has you covered.

 $\mbox{ \bullet}$  Automatic pressure equalization valve - balances interior pressure, keeps water out

- Fold down over-molded handle
- Stainless steel padlock protectors

• Super-light proprietary HPX Polymer makes this case up to 40% lighter than the competition

- Limited Lifetime Warranty
- Super-light proprietary HPX<sup>2</sup><sup>™</sup> Polymer up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck<sup>™</sup> foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified

# CONFIGURATIONS



1506 Standard



1506WF With Foam



**1506NF** No Foam



**1506TP** With TrekPak Divider System

### DIMENSIONS

Interior (L×W×D)	18.70 x 9.40" x 7.80 (47.5 x 23.9 x 19.8 cm)
Exterior (L×W×D)	20.12 x 12.02" x 8.56 (51.1 x 30.5 x 21.7 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	5.80" (14.7 cm)
Total Depth	7.8" (19.8 cm)
Int Volume	0.79 ft <sup>3</sup> (0.022 m <sup>3</sup> )
Padlock Hole Diameter	0.31" (0.8 cm)

#### MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Purge Body	ABS

#### Purge Vent

# COLOURS

Black

#### WEIGHT

Weight With Foam	6.30 lbs (2.9 kg)
Weight Empty	5.35 lbs (2.4 kg)
Buoyancy	51.69 lbs (23.4 kg)

### TEMPERATURE

Minimum Temperature	0°F (-17.8 °C)
Maximum Temperature	140°F (60 °C)

# ACCESSORIES





**1506AirFS** 4 pc. Replacement Foam Set

**1506TPKIT** TrekPak Case Divider Kit



RucPac-Pro-1 RucPac Pro Hardcase Backpack Conversion

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 08-10-25