



# 1780HL

## Protector

Rifle Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Fits M4, M16 firearms**
- **Watertight, crushproof, and dustproof**
- Detachable halves serve as mobile firearm racks
- Fast loading, lockable metal cross bar
- Humidity gauge changes color above 40%
- Manual Pressure Equalization Valve
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Rigid polyethylene tray option for 12 firearms
- 4 heavy duty polyurethane wheels with stainless steel bearings for one-man mobility



## DIMENSIONS

<b>Interior (L×W×D)</b>	41.12 x 21.54" x 14.88 (104.4 x 54.7 x 37.8 cm)
<b>Exterior (L×W×D)</b>	44.90 x 25.32" x 16.50 (114 x 64.3 x 41.9 cm)
<b>Lid Depth</b>	7.58" (19.3 cm)
<b>Bottom Depth</b>	7.30" (18.5 cm)
<b>Total Depth</b>	14.88" (37.8 cm)
<b>Int Volume</b>	7.63 ft³ (0.216 m³)
<b>Padlock Hole Diameter</b>	5/16" (12.7 cm)

## MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	EXL
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3 lb Polyurethane

## COLOURS

■ Black

## WEIGHT

<b>Weight With Foam</b>	68.40 lbs (31 kg)
<b>Weight Empty</b>	53.00 lbs (24 kg)
<b>Buoyancy</b>	500.00 lbs (226.8 kg)
<b>Master Pack Weight</b>	77.00 lbs (34.9 kg)

TEMPERATURE

---

**Minimum Temperature**    -40°F (-40 °C)  
**Maximum Temperature**    190°F (87.8 °C)

CERTIFICATIONS

---

**Def Stan 81-41**

OTHER

---

**Wheels**                                4  
**Master Pack**                        1  
**Nameplate**                        yes

ACCESSORIES

---



**1781**  
6 pc. Replacement Foam Set



**1783**  
Replacement O-ring



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

**Peli**  
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 07-31-25*