



1150 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1150
Standard



1150NF
No Foam



1150WF
With Foam






DIMENSIONS

| | |
|------------------------------|--|
| Interior (L×W×D) | 8.29 x 5.79" x 3.75 (21.1 x 14.7 x 9.5 cm) |
| Exterior (L×W×D) | 9.44 x 7.80" x 4.29 (24 x 19.8 x 10.9 cm) |
| Lid Depth | 0.75" (1.9 cm) |
| Bottom Depth | 2.87" (7.3 cm) |
| Total Depth | 3.62" (9.2 cm) |
| Int Volume | 0.1 ft³ (0.003 m³) |
| Padlock Hole Diameter | 0.19" (0.5 cm) |

MATERIALS

| | |
|-------------------|--------------------------------|
| Body | Polypropylene |
| Latch | Polypropylene |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLOURS

| | | | |
|--|--|--|--|
|  Black |  Blue |  Orange |  Silver |
|  Yellow | | | |

WEIGHT

| | |
|---------------------------|--------------------|
| Weight With Foam | 1.75 lbs (0.8 kg) |
| Weight Empty | 1.61 lbs (0.7 kg) |
| Buoyancy | 8.00 lbs (3.6 kg) |
| Master Pack Weight | 13.95 lbs (6.3 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 190°F (87.8 °C) |







CERTIFICATIONS

| | |
|-----------------------|--|
| IP67 | |
| Def Stan 81-41 | |

OTHER

| | |
|--------------------|-----|
| Master Pack | 6 |
| Military | yes |

ACCESSORIES

| | | | | |
|--|--|---|--|---|
|  1151 3 pc. Replacement Foam Set |  1153 Replacement O-ring |  1150PF Special Application Panel Frame |  1507 Quick Mounts - set of 4 |  1506TSA TSA Lock |
|  1500D Desiccant Silica Gel | | | | |