

1607 _{Air}

Peli[™] Air cases are the first in a series of remarkable innovations engineered by Peli, the pioneers of protective cases. For over 45 years Peli has designed and crafted the most influential protective cases in the world, and we're just getting started.

With the launch of the Peli[™] Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

 $\mbox{ \bullet}$ Automatic pressure equalization valve - balances interior pressure, keeps water out

- Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- Business card holder
- Quiet rolling stainless-steel bearing wheels
- Press and Pull[™] Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX²[™] Polymer up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck[™] foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



CONFIGURATIONS



1607 Standard



1607NF No Foam



1607WD With Padded Dividers



1607WF With Foam

DIMENSIONS

Interior (L×W×D)	21.05 x 15.81" x 11.63 (53.5 x 40.2 x 29.5 cm)
Exterior (L×W×D)	24.13 x 18.80" x 13.25 (61.3 x 47.8 x 33.7 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	9.60" (24.4 cm)
Total Depth	11.6" (29.5 cm)
Int Volume	2.24 ft³ (0.063 m³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Purge Body	ABS

Purge Vent

COLOURS

Black	Orange	Silver	Yellow	
WEIGHT				
Weight With Foam	16.10 lbs (7.3 kg)			
Weight Empty	13.20 lbs (6 kg)			
Buoyancy	178.00 lbs (80.7 kg)			

Minimum Temperature 0°F (-17.8 °C)

Minimum Temperature	0°F (-17.8 °C)
Maximum Temperature	140°F (60 °C)

2

OTHER

ACCESSORIES



Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 08-29-25