



## 2460Z1 StealthLite™

The rechargeable version of the StealthLite™ 2410 LED. The StealthLite™ Rechargeable 2460Z1 LED uses the 2469P NiMH battery and comes with the charger base unit cat # 2480F that can be installed at home or work using the 220V transformer cat # 2468Z1. Certified to ATEX Zone 1 (Category 2). Note, this charger base does not work on 12v systems.



### DIMENSIONS

<b>Length</b>	7.00" (17.8 cm)
---------------	-----------------

### MATERIALS

<b>Body</b>	Anti-static Impact Modified PC/PBT
<b>O-Ring</b>	Ethylene Propylene
<b>Lens</b>	Polycarbonate (PC)
<b>Shroud</b>	Anti-static Impact Modified PC/PBT
<b>Contact Spring Retainer</b>	Stainless Steel / Phosphore Bronze

### COLOURS

 High Visibility Yellow
--

### LIGHT SPECS

<b>Lamp Type</b>	LED
------------------	-----

### POWER

<b>Battery Size</b>	AA
<b>Battery Type</b>	NiMH
<b>Battery Quantity</b>	4
<b>Batteries Included</b>	yes
<b>Rechargeable</b>	yes
<b>Charge Time</b>	8 hrs
<b>Volts</b>	4.8v

### WEIGHT

<b>Weight With Batteries</b>	7.8 oz (221 gr)
<b>Weight Without Batteries</b>	4.4 oz (125 gr)
<b>Packaged Weight</b>	1.4 oz (40 gr)

### SWITCH

<b>Switch Type</b>	One-handed Safety Switch
<b>Light Modes</b>	On / Off

CERTIFICATIONS

ATEX Zone 1	
OTHER	

Minimum Pack	1
Military	yes
Package Code	C

FL1 STANDARD	HIGH
	181 LUMENS
	5h 0mins
	181m
	8235cd
	IPX7

ACCESSORIES



**0770**  
Helmet Light Holder



**2480F**  
Deck/Dash Charger Base Unit



**2469P**  
Replacement Battery

[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 01-16-26*