



0350 Protector Cube Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Large 2-person fold down handles**
- **Watertight, crushproof, and dustproof**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



0350
Standard



0354
With Padded Dividers



0350NF
No Foam



0350WF
With Foam

DIMENSIONS

| | |
|------------------------------|--|
| Interior (LxWxD) | 20.00 x 20.00" x 20.00 (50.8 x 50.8 x 50.8 cm) |
| Exterior (LxWxD) | 22.50 x 22.43" x 21.25 (57.2 x 57 x 54 cm) |
| Lid Depth | 5.00" (12.7 cm) |
| Bottom Depth | 15.00" (38.1 cm) |
| Total Depth | 20" (50.8 cm) |
| Int Volume | 4.63 ft³ (0.131 m³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| | |
|---------------|---------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |

| | |
|-------------------|--------------------------------|
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLOURS

■ Black

WEIGHT

| | |
|---------------------------|---------------------|
| Weight With Foam | 32.01 lbs (14.5 kg) |
| Weight Empty | 25.99 lbs (11.8 kg) |
| Buoyancy | 268.96 lbs (122 kg) |
| Master Pack Weight | 33.89 lbs (15.4 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

IP67
Def Stan 81-41

OTHER

| | |
|---------------------|-----|
| Master Pack | 1 |
| Nameplate | yes |
| Reduced Area | yes |
| Military | yes |

ACCESSORIES



0351
7 pc. Replacement Foam Set



0353
Replacement O-ring



0355
Padded Divider Set



0357
Cube Case Mobility Package



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 07-17-24