



## 9430

Remote Area Lighting Systems from Peli are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Peli tough
- New improved version - Generation 3
- Up to 15 hours of run time
- 3000 lumens of brightness
- Fully extendable mast with 360 degree rotating head
- Low Battery Warning System
- Waterproof Rubber Activation Switch
- Mast Extension Lock
- RoHS and CE Compliant



### DIMENSIONS

|                                |  |
|--------------------------------|--|
| <b>Head (LxWxD)</b>            | 6.50 x 7.87" x 2.56 (16.5 x 20 x 6.5 cm) |
| <b>Closed (LxWxD)</b>          | 15.75 x 7.87" x 9.06 (40 x 20 x 23 cm)   |
| <b>Light Head Height (max)</b> | 32.28" (82 cm)                           |
| <b>Cord Length</b>             | 13.78" (35 cm)                           |

### MATERIALS

|             |                          |
|-------------|--------------------------|
| <b>Body</b> | Polycarbonate (PC) / ABS |
| <b>Head</b> | Polycarbonate (PC) / ABS |
| <b>Mast</b> | Glass-Reinforced Plastic |
| <b>Lens</b> | Polycarbonate (PC)       |

### COLOURS

|   |  |
|---|--|
|  Black |  Yellow |
|---|--|

### LIGHT SPECS

|                       |      |
|-----------------------|------|
| <b>Lumens (High)</b>  | 3000 |
| <b>Lumens (Low)</b>   | 1500 |
| <b>Lamp Heads</b>     | 1    |
| <b>Lamp Type</b>      | LED  |
| <b>Number of LEDs</b> | 6    |
| <b>Beam Spread</b>    | 125° |
| <b>IP Rating</b>      | 54   |

### POWER

|                                |                        |
|--------------------------------|------------------------|
| <b>Run Time (High)</b>         | 8.00 hrs               |
| <b>Run Time (Low)</b>          | 15.00 hrs              |
| <b>Battery Type</b>            | Sealed Lead Acid (SLA) |
| <b>Rechargeable</b>            | yes                    |
| <b>Battery Lifespan</b>        | 500 cycles             |
| <b>Battery Level Indicator</b> | Intermittent Blinking  |

|                          |       |
|--------------------------|-------|
| <b>Sockets (Primary)</b> | 1     |
| <b>Sockets (Aux)</b>     | 1     |
| <b>Volts</b>             | 12.0v |

---

## WEIGHT

|               |                     |
|---------------|---------------------|
| <b>Weight</b> | 22.65 lbs (10.3 kg) |
|---------------|---------------------|

---

## SWITCH

|                    |                        |
|--------------------|------------------------|
| <b>Switch Type</b> | Silicone Rubber Keypad |
|--------------------|------------------------|

---

## ACCESSORIES



**1460AALG**  
1460 Case with custom fit foam



**9430TP**  
Tripod



**9436B**  
12/24V Vehicle Charger



**9437B**  
Extension Cord (black connector)  
118in (3m)

---

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 07-17-24*