



## 2315Z0

The hazard horizon is bright. With ATEX Zone 0 (Category 1) Safety Certification, 115 lumens, 75 meters of spot beam distance and an IPX8 Waterproof rating, the Peli™ 2315Z0 flashlight stretches light across dark, hazardous environments without being a source of ignition.

Engineered with an aluminum core and ABS overmoulded plastic, this flashlight is built for rough handling and can survive hard drops. Plus, the sturdy clip attaches to a work vest for fast access and the tail switch activates raw LED power, even when using heavy-duty work gloves.

**Peli™ 2315Z0 - SEE THE LIGHT AT THE END OF THE TUNNEL**

- Built Peli tough
- 2 AA Batteries (included)
- ATEX Safety Certified Zone 0 (Cat. 1)
- Integrated Clip
- Full / Momentary Activation Tail Switch
- IPX8 1m waterproof
- Helmet mount (included)



### DIMENSIONS

---

<b>Length</b>	6.22" (15.8 cm)
---------------	-----------------


### MATERIALS

---

<b>Body</b>	ABS
<b>O-Ring</b>	NBR
<b>Lens</b>	PC
<b>Shroud</b>	ABS
<b>Clip</b>	ABS

### COLOURS

---

 High Visibility Yellow
--

### LIGHT SPECS

---

<b>Lamp Type</b>	LED
------------------	-----

### POWER

---

<b>Battery Size</b>	AA
<b>Battery Type</b>	Alkaline
<b>Battery Quantity</b>	2
<b>Batteries Included</b>	yes
<b>Volts</b>	3.0v

### WEIGHT

---

<b>Weight With Batteries</b>	4.6 oz (130 gr)
<b>Weight Without Batteries</b>	2.8 oz (79 gr)

## SWITCH






---

**Switch Type** Momentary Push Button  
**Light Modes** High

## CERTIFICATIONS

---

**IECEX ia**  
**ATEX Zone 0**

FL1 STANDARD	HIGH
	115 LUMENS
	6h 0mins
	75m
	1403cd
	IPX8 (1m)

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 05-05-26*