



# 1495CC1

## Protector

### Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **3 dial combination lock included**
- **Fits up to 17" laptops**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down over-molded handle
- Lid organizer, shock absorbing tray, and padded shoulder strap
- Nylon padded computer sleeve and accessories pouch
- Stainless steel padlock protectors



## DIMENSIONS

<b>Interior (LxWxD)</b>	18.87 x 13.12" x 3.81 (47.9 x 33.3 x 9.7 cm)
<b>Exterior (LxWxD)</b>	21.62 x 17.25" x 4.87 (54.9 x 43.8 x 12.4 cm)
<b>Lid Depth</b>	1.12" (2.8 cm)
<b>Bottom Depth</b>	2.68" (6.8 cm)
<b>Total Depth</b>	3.8" (9.7 cm)
<b>Int Volume</b>	0.55 ft <sup>3</sup> (0.016 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	5/16" (12.7 cm)

## MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3 lb Polyurethane
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

## COLOURS

■ Black

## WEIGHT

<b>Weight With Foam</b>	11.10 lbs (5.03 kg)
<b>Buoyancy</b>	45.15 lbs (20.48 kg)
<b>Master Pack Weight</b>	28.00 lbs (12.7 kg)

TEMPERATURE

<b>Minimum Temperature</b>	-40°F (-40 °C)
<b>Maximum Temperature</b>	190°F (87.8 °C)

CERTIFICATIONS

<b>IP67</b>
<b>Def Stan 81-41</b>

OTHER

<b>Master Pack</b>	2
<b>Nameplate</b>	yes

ACCESSORIES



**1483**  
Replacement O-ring



**1495ALI**  
Attache/Computer Lid Insert



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

**Peli**  
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 01-31-26