

# 1670

# **Protector**

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- 4 strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- 2 level Pick N Pluck<sup>™</sup> with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Two oversized fold down handles for extra grip
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



#### **CONFIGURATIONS**



**1670** Standard



**1670NF** No Foam



**1670WF** With Foam



**1674**With Padded Dividers

# **DIMENSIONS**

Interior (L×W×D) 28.10 x 16.49" x 9.19 (71.4 x 41.9 x 23.3 cm) Exterior (L×W×D) 31.04 x 19.39" x 11.17 (78.8 x 49.3 x 28.4 cm)

 Lid Depth
 1.80" (4.6 cm)

 Bottom Depth
 7.39" (18.8 cm)

 Total Depth
 9.19" (23.3 cm)

 Int Volume
 2.46 ft³ (0.07 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

# **MATERIALS**

**Body** Polypropylene

LatchABSO-RingPolymerPinsStainless Steel

**Foam** 1.3 lb Polyurethane

Purge Body A

**Purge Vent** 3 Micron Hydrophobic Non-Woven

# **COLOURS**



#### WEIGHT

 Weight With Foam
 26.00 lbs (11.8 kg)

 Weight Empty
 23.00 lbs (10.4 kg)

 Buoyancy
 182.00 lbs (82.6 kg)

 Master Pack Weight
 49.00 lbs (22.2 kg)


# **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

# **OTHER**

Wheels 4 Master Pack 1

# **ACCESSORIES**



**1671** 4 pc. Replacement Foam Set



**1507** Quick Mounts - set of 4



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel

#### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 08-24-25