



## 1535

### Air

#### Carry-On Case

Peli™ Air cases are the toughest and lightest cases Peli has to offer. Designed with a super-light proprietary HPX<sup>2</sup> polymer construction, each Peli Air case is up to 40 percent lighter than an average polymer case, yet still extremely durable. Peli Air cases are waterproof, crushproof, and dustproof.

The Peli 1535 Air Case provides protection for a wide variety of gear, from camera equipment to camping kits. It is available with foam, without foam, padded dividers, or TrekPak dividers. The Peli 1535 Air Case is the maximum airline carry-on size, so you can travel with your sensitive gear close at hand. This Peli Air case will lighten the load, while protecting your valued possessions.

(Check with your airline for exact measurement requirements)

- Crushproof, watertight, and dustproof (IP67)
- Super-light proprietary HPX<sup>2</sup>™ polymer – up to 40% lighter than traditional cases
- Press and Pull™ latches for secure closure
- Retractable extension trolley handle for easy transport
- Quiet rolling stainless steel bearing wheels
- Foldable, ergonomic rubber handles
- User-customizable Pick N Pluck™ foam interior
- Waterproof O-ring seal
- Automatic pressure equalization valve – balances interior pressure, keeps water out
- Stainless steel padlock protectors and hardware
- Business card holder for personal or professional ID
- MIL-SPEC certified for professional-grade protection
- Use as dry box, lock box, suitcase, or toolbox
- Ideal for cameras, lenses, laptops, and tools
- Peli™ Limited Lifetime Guarantee



#### CONFIGURATIONS



#### DIMENSIONS

|                              |   |
|------------------------------|---|
| <b>Interior (L×W×D)</b>      | 20.39 x 11.20" x 7.21 (51.8 x 28.4 x 18.3 cm) |
| <b>Exterior (L×W×D)</b>      | 21.96 x 13.97" x 8.98 (55.8 x 35.5 x 22.8 cm) |
| <b>Lid Depth</b>             | 2.00" (5.1 cm)                                |
| <b>Bottom Depth</b>          | 5.21" (13.2 cm)                               |
| <b>Total Depth</b>           | 7.21" (18.3 cm)                               |
| <b>Int Volume</b>            | 0.95 ft <sup>3</sup> (0.027 m <sup>3</sup> )  |
| <b>Padlock Hole Diameter</b> | 0.31" (0.8 cm)                                |

#### MATERIALS

##### Body

Proprietary Polypropylene Blend

|                   |   |
|-------------------|---|
| <b>Latch</b>      | ABS   |
| <b>O-Ring</b>     | EPDM  |
| <b>Purge Body</b> | ABS   |
| <b>Purge Vent</b> | Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven |

## COLOURS

|           |                |               |               |
|-----------|----------------|---------------|---------------|
| ■ Black   | ■ Orange       | ■ Silver      | ■ White       |
| ■ Yellow  | ■ Graphite     | ■ Sage / Gray | ■ French Blue |
| ■ OCP Tan | ■ Hunter Green |               |               |

## WEIGHT

|  |                      |
|--|----------------------|
| <b>Weight With Foam</b>                  | 9.98 lbs (4.53 kg)   |
| <b>Weight Empty</b>                      | 8.69 lbs (3.94 kg)   |
| <b>Buoyancy</b>                          | 64.80 lbs (29.39 kg) |
| <b>Weight With TrekPak / Foam Hybrid</b> | 11.91 lbs (5.4 kg)   |

## TEMPERATURE

|                            |                |
|----------------------------|----------------|
| <b>Minimum Temperature</b> | 0°F (-17.8 °C) |
| <b>Maximum Temperature</b> | 140°F (60 °C)  |

## OTHER

|               |   |
|---------------|---|
| <b>Wheels</b> | 2 |
|---------------|---|

## ACCESSORIES



**1535AirFS**  
5 pc. Replacement Foam Set



**1535AirDS**  
Padded Divider Set



**1535TP-KIT**  
TrekPak Case Divider Kit



**1510TPDIV**  
Extra TrekPak Dividers



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**1535MP**  
EZ-Click™ MOLLE Panel



**RucPac-Pro-1**  
RucPac Pro Hardcase  
Backpack Conversion



**RucPac-normal**  
RucPac Standard Hardcase  
Backpack Conversion



**AIRHANDL**  
EZ-Pull Multi-Stage Air Handle



**1535TPDIV**  
Extra TrekPak Dividers

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 02-12-26*