

1690

Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- 4 strong polyurethane wheels with stainless steel bearings
- Large 2-person fold down handles
- Watertight, crushproof, and dustproof
- 3 level Pick N Pluck™ with convoluted lid foam
 Automatic pressure equalization valve balances interior pressure, keeps
- · Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel padlock protectors



CONFIGURATIONS



1690 Standard



1694 With Padded Dividers



1690NF No Foam



1690WF With Foam

DIMENSIONS

Interior (L×W×D) 30.13 x 25.13" x 15.36 (76.5 x 63.8 x 39 cm) 33.43 x 28.40" x 17.65 (84.9 x 72.1 x 44.8 cm) Exterior (L×W×D)

Lid Depth 2.86" (7.3 cm) **Bottom Depth** 12.14" (30.8 cm) **Total Depth** 15" (38.1 cm) **Int Volume** 6.73 ft3 (0.191 m3) Padlock Hole Diameter 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

Latch ABS **O-Ring** Polymer Pins Stainless Steel **Foam** 1.3 lb Polyurethane Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS



WEIGHT

 Weight With Foam
 43.00 lbs (19.5 kg)

 Weight Empty
 34.00 lbs (15.4 kg)

 Buoyancy
 433.00 lbs (196.4 kg)

 Master Pack Weight
 52.27 lbs (23.7 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Wheels 4
Extendable Handle yes
Master Pack 1
Nameplate yes
Reduced Area yes

ACCESSORIES



1691 5 pc. Replacement Foam Set



1693 Replacement O-ring



1695 Padded Divider Set



1699 Lid Organizer



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel

Document created on 05-08-24