



## 5050R

Get local to long distance in a slide. The new Peli™ 5050R flashlight features flood to spot technology: Flood position projects a wide beam to illuminate your work area and spot beam for a long distance focused beam. Get power for the work day and your smartphone. Recharge the 5050R by connecting directly to its Micro USB port. Or connect to a USB port to power your smartphone or any other USB powered device. The 5050R: it's our rechargeable option that can add some jolt to your text conversations.

- Lithium Ion Rechargeable Battery
- 4 modes: Boost / High / Low / Flashing
- Up to 201m Beam Distance
- Up to 883 Lumens



### DIMENSIONS

|        |                 |
|--------|-----------------|
| Length | 6.16" (15.6 cm) |
|--------|-----------------|

### MATERIALS

|        |                                |
|--------|--------------------------------|
| Body   | Aluminum with Type II Anodized |
| O-Ring | NBR                            |
| Lens   | AR Coated Glass                |
| Shroud | Aluminum with Type II Anodized |

### COLOURS

|         |
|---------|
| ■ Black |
|---------|

### LIGHT SPECS

|           |     |
|-----------|-----|
| Lamp Type | LED |
|-----------|-----|

### POWER


|                         |                             |
|-------------------------|-----------------------------|
| Battery Size            | 18650                       |
| Battery Type            | Lithium                     |
| Battery Quantity        | 1                           |
| Batteries Included      | yes                         |
| Rechargeable            | yes                         |
| Charge Time             | 6 hrs                       |
| Battery Level Indicator | Full-time battery indicator |
| Volts                   | 3.7v                        |

### WEIGHT

|                          |                 |
|--------------------------|-----------------|
| Weight With Batteries    | 5.8 oz (164 gr) |
| Weight Without Batteries | 4.1 oz (116 gr) |

SWITCH

|             |                               |
|-------------|-------------------------------|
| Switch Type | Push Button                   |
| Light Modes | Boost / High / Low / Flashing |

| FL1 STANDARD                                                                        | HIGH          | LOW          | BOOST         |
|-------------------------------------------------------------------------------------|---------------|--------------|---------------|
|    | 393<br>LUMENS | 21<br>LUMENS | 883<br>LUMENS |
|    | 2h 30mins     | 40h 0mins    | 0h 0mins      |
|    | 134m          | 30m          | 201m          |
|   | 4488cd        | 224cd        | 10093cd       |
|  | IPX8 (1m)     |              |               |

ACCESSORIES



**2389**  
Replacement Battery