



1607

Air

Peli™ Air cases are the first in a series of remarkable innovations engineered by Peli, the pioneers of protective cases. For over 40 years Peli has designed and crafted the most influential protective cases in the world, and we're just getting started.

With the launch of the Peli™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic Purge Valve - Keeps water and dust out while balancing air pressure
- **Watertight, crushproof, and dustproof**
- Super-light proprietary HPX2™ Polymer
- Business card holder



CONFIGURATIONS



1607
Standard



1607NF
No Foam



1607WD
With Padded Dividers



1607WF
With Foam

DIMENSIONS

Interior (L×W×D)	21.05 x 15.81" x 11.63 (53.5 x 40.2 x 29.5 cm)
Exterior (L×W×D)	24.13 x 18.80" x 13.25 (61.3 x 47.8 x 33.7 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	9.60" (24.4 cm)
Total Depth	11.6" (29.5 cm)
Int Volume	2.24 ft ³ (0.063 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

Black	Yellow	Silver	Orange
-------	--------	--------	--------

WEIGHT

Weight With Foam	16.10 lbs (7.3 kg)
Weight Empty	13.20 lbs (6 kg)
Buoyancy	178.00 lbs (80.7 kg)

TEMPERATURE

Minimum Temperature	-60°F (-51.1 °C)
Maximum Temperature	160°F (71.1 °C)

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

info@peli.com • www.peli.com

FOAM PROPERTIES

Layer 1 (Lid)	2.03" Convolute
Layer 2 (Base)	2.66" Pick N Pluck
Layer 3 (Base)	2.66" Pick N Pluck
Layer 4 (Base)	2.66" Pick N Pluck
Layer 5 (Base)	1.44" Pad

Document created on 09-16-19

OTHER

Wheels	2
---------------	---

ACCESSORIES