



# iM2100

## Storm

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- **Watertight, crushproof, and dustproof**

- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



### CONFIGURATIONS



**iM2100**  
Standard



**iM2100-X0000**  
No Foam



**iM2100-X0002**  
With Padded Dividers



**iM2100-X0001**  
With Foam

### DIMENSIONS

<b>Interior (LxWxD)</b>	13.00 x 9.20" x 6.00 (33 x 23.4 x 15.2 cm)
<b>Exterior (LxWxD)</b>	14.20 x 11.40" x 6.50 (36.1 x 29 x 16.5 cm)
<b>Lid Depth</b>	2.00" (5.1 cm)
<b>Bottom Depth</b>	4.00" (10.2 cm)
<b>Total Depth</b>	6" (15.2 cm)
<b>Int Volume</b>	0.42 ft <sup>3</sup> (0.012 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	1/4" (2.5 cm)

### MATERIALS

<b>Body</b>	Injection Molded HPX™ high performance resin
<b>Latch</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Latch (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>O-Ring</b>	EPDM
<b>Pins</b>	Stainless Steel
<b>Pins (Alt)</b>	Aluminum
<b>Foam</b>	1.3/1.35 polyester
<b>Purge Body</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Purge Body (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>Purge Vent</b>	Gortex membrane

### COLOURS

Black	Yellow	OD Green	Realtree Edge
-------	--------	----------	---------------

### WEIGHT

<b>Weight With Foam</b>	4.90 lbs (2.2 kg)
-------------------------	-------------------

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

**Weight Empty** 4.20 lbs (1.9 kg) [info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)  
**Buoyancy** 26.20 lbs (11.9 kg)  
**Master Pack Weight** 24.60 lbs (11.2 kg) *Document created on 09-19-19*

TEMPERATURE

**Minimum Temperature** -20°F (-28.9 °C)  
**Maximum Temperature** 140°F (60 °C)

CERTIFICATIONS

MIL-STD-810F  
ATA 300  
FED-STD-101C

FOAM PROPERTIES

**Layer 1 (Lid)** 2.00" Convolute  
**Layer 2 (Base)** 0.63" Pad  
**Layer 3 (Base)** 1.69" Pick N Pluck  
**Layer 4 (Base)** 1.69" Pick N Pluck

OTHER

**Master Pack** 4  
**Military** yes

---

ACCESSORIES