



iM2450

Storm

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- **Watertight, crushproof, and dustproof**

- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



CONFIGURATIONS



iM2450
Standard



iM2450-X0000
No Foam



iM2450-X0002
With Padded Dividers



iM2450-X0001
With Foam

DIMENSIONS

Interior (LxWxD)	18.00 x 13.00" x 8.40 (45.7 x 33 x 21.3 cm)
Exterior (LxWxD)	19.20 x 15.20" x 9.00 (48.8 x 38.6 x 22.9 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	6.40" (16.3 cm)
Total Depth	8.4" (21.3 cm)
Int Volume	1.14 ft ³ (0.032 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

COLOURS

- Black
- OD Green

WEIGHT

Weight With Foam	8.90 lbs (4 kg)
-------------------------	-----------------

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

Weight Empty 7.40 lbs (3.4 kg) info@peli.com • www.peli.com
Buoyancy 70.86 lbs (32.1 kg)
Master Pack Weight 31.00 lbs (14.1 kg) *Document created on 09-15-19*

TEMPERATURE

Minimum Temperature -20°F (-28.9 °C)
Maximum Temperature 140°F (60 °C)

CERTIFICATIONS

MIL-STD-810F
ATA 300
FED-STD-101C

FOAM PROPERTIES

Layer 1 (Lid) 2.00" Convolute
Layer 2 (Base) 0.63" Pad
Layer 3 (Base) 1.88" Pick N Pluck
Layer 4 (Base) 1.88" Pick N Pluck
Layer 5 (Base) 2.00" Pick N Pluck

OTHER

Master Pack 3
Military yes

ACCESSORIES