



# iM2620

## Storm

Travel Case

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

• **Watertight, crushproof, and dustproof**

- Trolley handle & wheel system
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



### CONFIGURATIONS



**iM2620**  
Standard



**iM2620-X0000**  
No Foam



**iM2620-X0002**  
With Padded Dividers



**iM2620-X0006**  
With TrekPak Divider System



**iM2620-X0001**  
With Foam

### DIMENSIONS

<b>Interior (LxWxD)</b>	20.00 x 14.00" x 10.00 (50.8 x 35.6 x 25.4 cm)
<b>Exterior (LxWxD)</b>	21.20 x 16.00" x 10.60 (53.8 x 40.6 x 26.9 cm)
<b>Lid Depth</b>	2.00" (5.1 cm)
<b>Bottom Depth</b>	8.00" (20.3 cm)
<b>Total Depth</b>	10" (25.4 cm)
<b>Int Volume</b>	1.62 ft <sup>3</sup> (0.046 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	5/16" (12.7 cm)

### MATERIALS

<b>Body</b>	Injection Molded HPX™ high performance resin
<b>Latch</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Latch (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>O-Ring</b>	EPDM
<b>Pins</b>	Stainless Steel
<b>Pins (Alt)</b>	Aluminum
<b>Foam</b>	1.3/1.35 polyester
<b>Purge Body</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Purge Body (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>Purge Vent</b>	Gortex membrane

### COLOURS

- Black
- OD Green

### WEIGHT

<b>Weight With Foam</b>	14.50 lbs (6.6 kg)
-------------------------	--------------------

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

**Weight Empty** 12.50 lbs (5.7 kg) [info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)  
**Buoyancy** 101.62 lbs (46.1 kg)  
**Master Pack Weight** 14.50 lbs (6.6 kg) *Document created on 09-21-19*

TEMPERATURE

**Minimum Temperature** -20°F (-28.9 °C)  
**Maximum Temperature** 140°F (60 °C)

CERTIFICATIONS

MIL-STD-810F  
ATA 300  
FED-STD-101C

FOAM PROPERTIES

**Layer 1 (Lid)** 2.00" Convolute  
**Layer 2 (Base)** 0.50" Pad  
**Layer 3 (Base)** 2.00" Pick N Pluck  
**Layer 4 (Base)** 1.75" Pick N Pluck  
**Layer 5 (Base)** 1.75" Pick N Pluck  
**Layer 6 (Base)** 1.75" Pick N Pluck

OTHER

**Master Pack** 1  
**Military** yes

---

ACCESSORIES