



# iM2720

## Storm

Travel Case

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- Four Press & Pull Latches
- Two Padlockable Hasps
- Two Double-layered, Soft-grip Handles
- Two Integrated Key Lockable Latches
- Powerful Hinges
- O-ring seal
- Two stainless steel padlock protectors
- Specialized molded foam interior designed for Pump or Semi-automatic shotguns and accessories
- Retention Strap Instructions



### CONFIGURATIONS



**iM2720**  
Standard



**iM2720-X0000**  
No Foam



**iM2720-X0002**  
With Padded Dividers



**iM2720-X0006**  
With TrekPak Divider System



**iM2720-X0001**  
With Foam

### DIMENSIONS

<b>Interior (LxWxD)</b>	22.00 x 17.00" x 10.00 (55.9 x 43.2 x 25.4 cm)
<b>Exterior (LxWxD)</b>	24.60 x 19.70" x 11.70 (62.5 x 50 x 29.7 cm)
<b>Lid Depth</b>	2.00" (5.1 cm)
<b>Bottom Depth</b>	8.00" (20.3 cm)
<b>Total Depth</b>	10" (25.4 cm)
<b>Int Volume</b>	2.16 ft <sup>3</sup> (0.061 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	1/4" (2.5 cm)

### MATERIALS

<b>Body</b>	Injection Molded HPX™ high performance resin
<b>Latch</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Latch (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>O-Ring</b>	EPDM
<b>Pins</b>	Stainless Steel
<b>Pins (Alt)</b>	Aluminum
<b>Foam</b>	1.3/1.35 polyester
<b>Purge Body</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Purge Body (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>Purge Vent</b>	Gortex membrane

### COLOURS

- Black
- Yellow
- OD Green

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

**WEIGHT**

<b>Weight With Foam</b>	22.00 lbs (10 kg)	<i>Document created on 09-21-19</i>
<b>Weight Empty</b>	16.80 lbs (7.6 kg)	
<b>Buoyancy</b>	138.14 lbs (62.7 kg)	
<b>Master Pack Weight</b>	24.00 lbs (10.9 kg)	

**TEMPERATURE**

<b>Minimum Temperature</b>	-20°F (-28.9 °C)
<b>Maximum Temperature</b>	140°F (60 °C)

**CERTIFICATIONS**

MIL-STD-810F  
ATA 300  
FED-STD-101C

**FOAM PROPERTIES**

<b>Layer 1 (Lid)</b>	2.00" Convolute
<b>Layer 2 (Base)</b>	0.63" Pad
<b>Layer 3 (Base)</b>	1.88" Pick N Pluck
<b>Layer 4 (Base)</b>	1.88" Pick N Pluck
<b>Layer 5 (Base)</b>	1.88" Pick N Pluck

**OTHER**

<b>Extendable Handle</b>	yes
<b>Master Pack</b>	1
<b>Military</b>	yes

---

**ACCESSORIES**