



# iM2975

## Storm

Travel Case

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- Five Press & Pull Latches
- Two Padlockable Hasps
- Two Double-layered, Soft-grip Handles
- Two Integrated Key Lockable Latches
- Powerful Hinges
- O-ring seal
- Two stainless steel padlock protectors
- Specialized molded foam interior designed for Pump or Semi-automatic shotguns and accessories
- Retention Strap Instructions




### CONFIGURATIONS



**iM2975**  
Standard



**iM2975-X0000**  
No Foam



**iM2975-X0002**  
With Padded Dividers



**iM2975-X0001**  
With Foam

### DIMENSIONS

<b>Interior (LxWxD)</b>	29.00 x 18.00" x 13.80 (73.7 x 45.7 x 35.1 cm)
<b>Exterior (LxWxD)</b>	31.30 x 20.40" x 15.50 (79.5 x 51.8 x 39.4 cm)
<b>Lid Depth</b>	2.00" (5.1 cm)
<b>Bottom Depth</b>	11.80" (30 cm)
<b>Total Depth</b>	13.8" (35.1 cm)
<b>Int Volume</b>	4.17 ft <sup>3</sup> (0.118 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	1/4" (2.5 cm)

### MATERIALS

<b>Body</b>	Injection Molded HPX™ high performance resin
<b>Latch</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Latch (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>O-Ring</b>	EPDM
<b>Pins</b>	Stainless Steel
<b>Pins (Alt)</b>	Aluminum
<b>Foam</b>	1.3/1.35 polyester
<b>Purge Body</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Purge Body (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>Purge Vent</b>	Gortex membrane

### COLOURS

■ Black

■ OD Green

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

WEIGHT

<b>Weight With Foam</b>	29.50 lbs (13.4 kg)	<i>Document created on 09-15-19</i>
<b>Weight Empty</b>	22.80 lbs (10.3 kg)	
<b>Buoyancy</b>	250.02 lbs (113.4 kg)	
<b>Master Pack Weight</b>	31.50 lbs (14.3 kg)	

TEMPERATURE

<b>Minimum Temperature</b>	-20°F (-28.9 °C)
<b>Maximum Temperature</b>	140°F (60 °C)

CERTIFICATIONS

MIL-STD-810F  
ATA 300  
FED-STD-101C

FOAM PROPERTIES

<b>Layer 1 (Lid)</b>	2.00" Convolute
<b>Layer 2 (Base)</b>	0.63" Pad
<b>Layer 3 (Base)</b>	1.88" Pick N Pluck
<b>Layer 4 (Base)</b>	1.88" Pick N Pluck
<b>Layer 5 (Base)</b>	1.88" Pick N Pluck
<b>Layer 6 (Base)</b>	1.88" Pick N Pluck
<b>Layer 7 (Base)</b>	1.88" Pick N Pluck
<b>Layer 8 (Base)</b>	1.88" Pick N Pluck

OTHER

<b>Extendable Handle</b>	yes
<b>Master Pack</b>	1
<b>Military</b>	yes

---

ACCESSORIES