



iM3100

Storm

Long Case

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- Six Press & Pull Latches
- Two Padlockable Hasps
- Two Double-layered, Soft-grip Handles
- Vortex™ Valve
- Powerful Hinges
- O-ring seal
- Lightweight Strong HPX® Resin
- Retention Strap Instructions



CONFIGURATIONS



iM3100
Standard



iM3100-X0000
No Foam



iM3100-X0001
With Foam

DIMENSIONS

Interior (LxWxD)	36.50 x 14.00" x 6.00 (92.7 x 35.6 x 15.2 cm)
Exterior (LxWxD)	39.80 x 16.50" x 6.70 (101.1 x 41.9 x 17 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	4.00" (10.2 cm)
Total Depth	6" (15.2 cm)
Int Volume	1.77 ft ³ (0.05 m ³)
Padlock Hole Diameter	3/8" (7.6 cm)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

COLOURS

- Black
- OD Green

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

info@peli.com • www.peli.com

WEIGHT

Weight With Foam	19.80 lbs (9 kg)	<i>Document created on 09-16-19</i>
Weight Empty	15.20 lbs (6.9 kg)	
Buoyancy	113.07 lbs (51.3 kg)	
Master Pack Weight	8.00 lbs (3.6 kg)	

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

CERTIFICATIONS

MIL-STD-810F
ATA 300
FED-STD-101C

FOAM PROPERTIES

Layer 1 (Lid)	2.00" Convolute
Layer 2 (Base)	0.50" Pad
Layer 3 (Base)	1.75" Pad
Layer 4 (Base)	1.75" Pad

OTHER

Master Pack	1
Military	yes

ACCESSORIES