



# 1700 Protector

Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 3-piece foam set
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Easy open Double Throw latches
- Fold down side handle
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors



## CONFIGURATIONS



**1700**  
Standard



**1700NF**  
No Foam



**1700WF**  
With Foam

## DIMENSIONS

<b>Interior (LxWxD)</b>	35.75 x 13.50" x 5.25 (90.8 x 34.3 x 13.3 cm)
<b>Exterior (LxWxD)</b>	38.12 x 16.00" x 6.12 (96.8 x 40.6 x 15.5 cm)
<b>Lid Depth</b>	1.75" (4.4 cm)
<b>Bottom Depth</b>	3.50" (8.9 cm)
<b>Total Depth</b>	5.25" (13.3 cm)
<b>Int Volume</b>	1.47 ft <sup>3</sup> (0.042 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	5/16" (12.7 cm)

## MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3 lb Polyurethane
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

## COLOURS

- Black
- OD Green

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

WEIGHT

<b>Weight With Foam</b>	16.98 lbs (7.7 kg)	<i>Document created on 09-21-19</i>
<b>Weight Empty</b>	16.09 lbs (7.3 kg)	
<b>Buoyancy</b>	136.91 lbs (62.1 kg)	
<b>Master Pack Weight</b>	19.10 lbs (8.7 kg)	

TEMPERATURE

<b>Minimum Temperature</b>	-40°F (-40 °C)
<b>Maximum Temperature</b>	210°F (98.9 °C)

CERTIFICATIONS

IP67  
MIL C-4150J  
Def Stan 81-41  
STANAG 4280

FOAM PROPERTIES

<b>Layer 1 (Lid)</b>	1.63" Pad
<b>Layer 2 (Base)</b>	1.63" Pad
<b>Layer 3 (Base)</b>	1.63" Pad

OTHER

<b>Wheels</b>	2
<b>Master Pack</b>	1
<b>Military</b>	yes

---

ACCESSORIES