



3345Z0

Peli™ 3345Z0 with Automatic Light Sensor: The first professional torch that automatically adjusts brightness. It has a mind of its own. The Automatic Light Sensor in the Peli™ 3345Z0 examines the ambient light/proximity and instantly adjusts its lumens to the most effective level. Now you can read pressure gauges close up or throw light hundreds of meters away - without hassling over manual power settings. The Automatic Light Sensor also makes the Peli™ 3345Z0 one of our most energy efficient torches, preserving power and stretching battery life. Plus, the secondary flood beam illuminates potential trip hazards like loose cables, while the primary spot beam brightens long tunnels. The integrated clip can be mounted to a safety vest for hands-free lighting. With the ATEX Zone 0 (Cat. 1) safety certification and a full-time battery level indicator, you can work in hazardous areas with peace of mind.

- Full Time Battery Level Indication
- Dual Beams (Spot and Flood)
- 3 AA Alkaline Batteries (not included)
- Automatic Light Sensor (automatically adjusts to ambient light levels and proximity)
- Safety Certified ATEX Zone 0 (Category 1)
- Integrated Clip for Hands-Free Lighting
- Peli's Lifetime Guarantee (where applicable by law)




DIMENSIONS

| | |
|--------|-----------------|
| Length | 7.25" (18.4 cm) |
|--------|-----------------|

MATERIALS

| | |
|--------|---------------------------------------|
| Body | Anti-static Impact Modified PC/PBT |
| O-Ring | NBR |
| Lens | Anti-static coated Polycarbonate (PC) |
| Shroud | Anti-static Impact Modified PC/PBT |
| Clip | Anti-static Impact Modified PC/PBT |

COLOURS

| |
|--|
|  High Visibility Yellow |
|--|

LIGHT SPECS

| | |
|---------------------|-----|
| Lamp Type | LED |
| Lamp Secondary Type | LED |

POWER

| | |
|-------------------------|-----------------------------|
| Battery Size | AA |
| Battery Type | Alkaline |
| Battery Quantity | 3 |
| Battery Level Indicator | Full-time battery indicator |
| Volts | 4.5v |

WEIGHT






| | |
|---------------------------------|-----------------|
| Weight With Batteries | 7.5 oz (213 gr) |
| Weight Without Batteries | 5.0 oz (142 gr) |

SWITCH

| | |
|--------------------|-------------|
| Switch Type | Push Button |
| Light Modes | High |

CERTIFICATIONS

ATEX Zone 0

| FL1 STANDARD | SPOT / FLOOD | FLOOD | SPOT |
|---|---------------|---------------|---------------|
|  | 267 LUMENS | 115 LUMENS | 207 LUMENS |
|  | 5h 0mins | 13h 0mins | 9h 0mins |
|  | 126m | 16m | 134m |
|  | 4000cd | 61cd | 4523cd |
|  | IPX7 | | |

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 04-24-24