



3345Z0

Peli™ 3345Z0 with Automatic Light Sensor: The first professional torch that automatically adjusts brightness.

It has a mind of its own. The Automatic Light Sensor in the Peli™ 3345Z0 examines the ambient light/proximity and instantly adjusts its lumens to the most effective level. Now you can read pressure gauges close up or throw light hundreds of meters away - without hassling over manual power settings.

The Automatic Light Sensor also makes the Peli™ 3345Z0 one of our most energy efficient torches, preserving power and stretching battery life. Plus, the secondary flood beam illuminates potential trip hazards like loose cables, while the primary spot beam brightens long tunnels.

The integrated clip can be mounted to a safety vest for hands-free lighting. With the ATEX Zone 0 (Cat. 1) safety certification and a full-time battery level indicator, you can work in hazardous areas with peace of mind.

- Full Time Battery Level Indication
- Dual Beams (Spot and Flood)
- 3 AA Alkaline Batteries (not included)
- Automatic Light Sensor (automatically adjusts to ambient light levels and proximity)
- Safety Certified ATEX Zone 0 (Category 1)
- Integrated Clip for Hands-Free Lighting
- Peli's Lifetime Guarantee (where applicable by law)



DIMENSIONS

Length	7.25" (18.4 cm)
---------------	-----------------

MATERIALS

Body	Anti-static Impact Modified PC/PBT
O-Ring	NBR
Lens	Anti-static coated Polycarbonate (PC)
Shroud	Anti-static Impact Modified PC/PBT
Clip	Anti-static Impact Modified PC/PBT

COLOURS

 High Visibility Yellow

LIGHT SPECS

Lamp Type	LED
Lamp Secondary Type	LED

POWER

Battery Size	AA
Battery Type	Alkaline
Battery Quantity	3
Battery Level Indicator	Full-time battery indicator
Volts	4.5v

WEIGHT


Weight With Batteries	7.5 oz (213 gr)
Weight Without Batteries	5.0 oz (142 gr)

SWITCH

Switch Type	Push Button
Light Modes	High

CERTIFICATIONS

ATEX Zone 0

FL1 STANDARD	SPOT / FLOOD	FLOOD	SPOT
	267 LUMENS	115 LUMENS	207 LUMENS
	7h 0mins	14h 0mins	12h 0mins
	126m	16m	134m
	4000cd	61cd	4523cd
	IPX7		

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 04-03-20