



1465

Air

Peli™ Air cases are the first in a series of remarkable innovations engineered by Peli, the pioneers of protective cases. For over 45 years Peli has designed and crafted the most influential protective cases in the world, and we're just getting started.

With the launch of the Peli™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Fold down over-molded handle
- Stainless steel padlock protectors
- Press and Pull™ Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX²™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck™ foam
- Waterproof, crushproof, dustproof



DIMENSIONS

| | |
|------------------------------|--|
| Interior (LxWxD) | 18.62 x 9.99" x 10.93 (47.3 x 25.4 x 27.8 cm) |
| Exterior (LxWxD) | 20.83 x 12.62" x 12.75 (52.9 x 32.1 x 32.4 cm) |
| Lid Depth | 4.94" (12.5 cm) |
| Bottom Depth | 5.99" (15.2 cm) |
| Total Depth | 10.93" (27.8 cm) |
| Int Volume | 1.18 ft ³ (0.033 m ³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| | |
|-------------------|---|
| Body | Proprietary Polypropylene Blend |
| Latch | ABS |
| O-Ring | EPDM |
| Pins | Stainless Steel |
| Foam | Polyurethane |
| Purge Body | ABS |
| Purge Vent | Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven |

COLOURS

■ Black

WEIGHT

| | |
|-------------------------|---------------------|
| Weight With Foam | 8.78 lbs (4 kg) |
| Weight Empty | 7.12 lbs (3.2 kg) |
| Buoyancy | 82.00 lbs (37.2 kg) |

TEMPERATURE

Minimum Temperature -60°F (-51.1 °C)

Maximum Temperature 160°F (71.1 °C)

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

info@peli.com • www.peli.com

ACCESSORIES

Document created on 04-02-25