



# 1780

## Protector

### Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **4 strong polyurethane wheels with stainless steel bearings**
- **The new class of XXL Peli Transport Cases**
- **Watertight, crushproof, and dustproof**
- 50/50 lid-to-base ratio for easy loading
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Completely detachable lid for full access
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel padlock protectors
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



## CONFIGURATIONS



**1780**  
Standard



**1780NF**  
No Foam



**1780WF**  
With Foam

## DIMENSIONS

|                              |   |
|------------------------------|---|
| <b>Interior (L×W×D)</b>      | 41.12 x 21.54" x 14.88 (104.4 x 54.7 x 37.8 cm) |
| <b>Exterior (L×W×D)</b>      | 44.90 x 25.32" x 16.50 (114 x 64.3 x 41.9 cm)   |
| <b>Lid Depth</b>             | 7.58" (19.3 cm)                                 |
| <b>Bottom Depth</b>          | 7.30" (18.5 cm)                                 |
| <b>Total Depth</b>           | 14.88" (37.8 cm)                                |
| <b>Int Volume</b>            | 7.63 ft³ (0.216 m³)                             |
| <b>Padlock Hole Diameter</b> | 0.31" (0.8 cm)                                  |

## MATERIALS

|               |               |
|---------------|---------------|
| <b>Body</b>   | Polypropylene |
| <b>Latch</b>  | EXL           |
| <b>O-Ring</b> | Polymer       |

|                   |                                |
|-------------------|--------------------------------|
| <b>Pins</b>       | Stainless Steel                |
| <b>Foam</b>       | 1.3 lb Polyurethane            |
| <b>Purge Body</b> | ABS                            |
| <b>Purge Vent</b> | 3 Micron Hydrophobic Non-Woven |

## COLOURS

■ Black

## WEIGHT

|                           |                       |
|---------------------------|-----------------------|
| <b>Weight With Foam</b>   | 49.00 lbs (22.2 kg)   |
| <b>Weight Empty</b>       | 38.40 lbs (17.4 kg)   |
| <b>Buoyancy</b>           | 500.00 lbs (226.8 kg) |
| <b>Master Pack Weight</b> | 56.00 lbs (25.4 kg)   |

## TEMPERATURE

|                            |                 |
|----------------------------|-----------------|
| <b>Minimum Temperature</b> | -40°F (-40 °C)  |
| <b>Maximum Temperature</b> | 210°F (98.9 °C) |

## CERTIFICATIONS

**Def Stan 81-41**

## OTHER

|                    |     |
|--------------------|-----|
| <b>Wheels</b>      | 4   |
| <b>Master Pack</b> | 1   |
| <b>Nameplate</b>   | yes |

## ACCESSORIES



**1781**  
6 pc. Replacement Foam Set



**1783**  
Replacement O-ring



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 05-21-24