

2460Z1

StealthLite™

The rechargeable version of the StealthLite™ 2410 LED. The StealthLite™ Rechargeable 2460Z1 LED uses the 2469P NiMH battery and comes with the charger base unit cat # 2480F that can be installed at home or work using the 220V transformer cat # 2468Z1. Certified to ATEX Zone 1 (Category 2). Note, this charger base does not work on 12v systems.



DIMENSIONS

Length 7.00" (17.8 cm)

MATERIALS

Body Anti-static Impact Modified PC/PBT

O-Ring Ethylene Propylene **Lens** Polycarbonate (PC)

Shroud Anti-static Impact Modified PC/PBT **Contact Spring Retainer** Stainless Steel / Phosphore Bronze

COLOURS

High Visibility Yellow

LIGHT SPECS

Lamp Type LED

POWER

Battery Size AA
Battery Type NiMH
Battery Quantity 4
Batteries Included yes
Rechargeable yes
Charge Time 5 hrs
Volts 4.8v

WEIGHT

Weight With Batteries 7.8 oz (221 gr)
Weight Without
Batteries 4.4 oz (125 gr)
Packaged Weight 1.4 oz (40 gr)

SWITCH

Switch Type One-handed Safety Switch

Light Modes On / Off

ATEX Zone 1

OTHER

Minimum Pack1MilitaryyesPackage CodeC

FL1 STANDARD	HIGH
	181 LUMENS
Θ	5h 0mins
	181m
	8235cd
The second	IPX7

ACCESSORIES



0770 Helmet Light Holder



2480F Deck/Dash Charger Base Unit



2469P Replacement Battery

 $\underline{\mathsf{info@peli.com}} \bullet \underline{\mathsf{www.peli.com}}$

Document created on 05-21-24