

AL5924-1009

For over 65 years Peli's roto-molded cases have been relied upon for an unmatched range of engineered solutions for the Military and Medical, Telecommunications and High Tech industries. Peli offers over 350 case sizes with unlimited case configurations using standard case options. Either build your own case or our engineers will customize a solution specific to your performance requirements.

Our roto molded cases pass MIL-STD 810D and E, MIL-STD 810E MIL-STD-210C, ASTM E96; FED-STD-101 and ATA 300 testing.

This level of performance ensures your equipment is safe from any unforeseen elements when deploying, transporting or storing your most valuable assets.

- One-piece construction, molded from lightweight, high-impact polyethylene
- Molded-in, tongue-in-groove gasketed "parting lines" provide for weather resistance.
- Reinforced corners and edges for additional impact protection when cases are dropped.
- Hardware attaches to molded-in metal inserts to provide pull-out strength and load spreading so hardware never fails.
- Molded-in ribs and corrugations offer case strength for secure and heavy weight stacking capacity
- Recessed hardware, with its engineered shoulder geometry, reduces shear forces that prevents lid separation after impact and controls pressure on the gasket to maintain a weatherproof seal.



DIMENSIONES

INTERIOR 59.30 x 24.30" x 19.30 (150.6 x 61.7 x 49 cm) **EXTERIOR** 62.30 x 27.30" x 21.60 (158.2 x 69.3 x 54.9 cm)

profundidad tapa9.20" (23.4 cm)profundidad base10.10" (25.7 cm)profundidad total19.3" (49 cm)volumen interior16.09 ft³ (0.456 m³)

MATERIALES

espuma

cuerpoRotoMolded PolyethylenecierreSteel (Nickel-black Plated)

anillo de sellado de neopreno

Silicone Sponge

No Foam, empty case standard

Optional PE and PU, 1 and 2 lb. options filled and lined

cuerpo de compensación

Aluminum

asa Heavy Duty Injection Molded Standard

componentes metálicos Yellow Carbon Steel Standard

COLORES

PESO

peso

61.30 lbs (27.8 kg)

LA TEMPERATURA

 $\begin{array}{ll} \mbox{temperatura mı́nima} & -20\mbox{°F (-28.9 °C)} \\ \mbox{temperatura máxima} & 140\mbox{°F (60 °C)} \\ \end{array}$

OTRAS

Aplicaciones militares

Peli

Document created on 11-04-25