



## 9480

Remote Area Lighting Systems from Peli are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Peli tough
- 3 pre-set light output levels
- Up to 4,000 lumens (calculated)
- Up to 28 hrs of run time
- Full time battery level indication with low level flashing indicator
- Deployable mast with 340 degree rotation
- Multiple deployment positions
- Convenient shoulder strap
- Quick release / Hot swappable battery design with 12 volt power supply



### DIMENSIONS

<b>Head (LxWxD)</b>	8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm)
<b>Closed (LxWxD)</b>	15.50 x 6.50" x 10.25 (39.4 x 16.5 x 26 cm)
<b>Light Head Height (max)</b>	23.75" (60.3 cm)

### MATERIALS

<b>Body</b>	Polypropylene
<b>Head</b>	Aluminum
<b>Mast</b>	Aluminum
<b>Lens</b>	Polycarbonate (PC)

### COLOURS

 Black	 Yellow
---	--

### LIGHT SPECS

<b>Lumens (High)</b>	4000
<b>Lumens (Med)</b>	3000
<b>Lumens (Low)</b>	1000
<b>Lamp Heads</b>	1
<b>Lamp Type</b>	LED
<b>Number of LEDs</b>	8
<b>Beam Spread</b>	125°
<b>IP Rating</b>	54

### POWER

<b>Run Time (High)</b>	6.00 hrs
<b>Run Time (Med)</b>	8.00 hrs
<b>Run Time (Low)</b>	28.00 hrs
<b>Battery Type</b>	Sealed Lead Acid (SLA)

<b>Rechargeable</b>	yes
<b>Battery Lifespan</b>	500 cycles
<b>Charge Time</b>	8 hrs
<b>Battery Level Indicator</b>	Full-time battery level display and low battery warning (visible flashing)
<b>Sockets (Primary)</b>	1
<b>Volts</b>	12.0v

---

## WEIGHT

<b>Weight</b>	27.50 lbs (12.5 kg)
---------------	---------------------

---

## SWITCH


<b>Switch Type</b>	Silicone Rubber Keypad
<b>Light Modes</b>	High / Medium / Low / Flashing

---

## ACCESSORIES



**9447**  
DC Vehicle Charger Cord



**9483**  
Power Supply



**9487**  
Padded Shoulder Strap



**9489**  
Powerpack

---

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 03-31-25*