

9490

Remote Area Lighting Systems from Peli are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Peli tough
- Full time battery level indication with low level flashing indicator
- Deployable mast with 340 degree rotation
- Multiple deployment positions
- Convenient shoulder strap
- Quick release / Hot swappable battery design with 12 volt power supply
- Up to 6,000 lumens (calculated)
- Up to 24 hrs of run time
- Intelligent Control (allows for various light output levels)



DIMENSIONS

Head (L×W×D) 8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm) Closed (L×W×D) 20.00 x 6.50" x 11.25 (50.8 x 16.5 x 28.6 cm)

Light Head Height (max)

72.00" (182.9 cm)

MATERIALS

Body Polypropylene Aluminum Head Mast Aluminum

Polycarbonate (PC) Lens

COLOURS

Black Yellow

LIGHT SPECS

Lumens (High) 6000 **Lamp Heads** LED **Lamp Type** Number of LEDs 10 **Beam Spread** 125° **IP Rating** 54

POWER

Run Time (High) 3.50 hrs Run Time (Med) 12.00 hrs Run Time (Low) 24.00 hrs

Battery Type Sealed Lead Acid (SLA)

Rechargeable yes **Battery Lifespan** 500 cycles Charge Time 8 hrs

Battery Level Indicator Full-time battery level display and low battery warning (visible flashing)

Sockets (Primary) 1 Volts 12.0v

WEIGHT

Weight 32.00 lbs (14.5 kg)

SWITCH

Switch TypeSilicone Rubber KeypadLight ModesHigh / Medium / Low / Flashing

ACCESSORIES



9483 Power Supply



9487 Padded Shoulder Strap



9489 Powerpack



9447 DC Vehicle Charger Cord

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 11-01-25