



## 9490

Remote Area Lighting Systems from Peli are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Peli tough
- Full time battery level indication with low level flashing indicator
- Deployable mast with 340 degree rotation
- Multiple deployment positions
- Convenient shoulder strap
- Quick release / Hot swappable battery design with 12 volt power supply
- Up to 6,000 lumens (calculated)
- Up to 24 hrs of run time
- Intelligent Control (allows for various light output levels)



### DIMENSIONS

|                                |   |
|--------------------------------|---|
| <b>Head (LxWxD)</b>            | 8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm)      |
| <b>Closed (LxWxD)</b>          | 20.00 x 6.50" x 11.25 (50.8 x 16.5 x 28.6 cm) |
| <b>Light Head Height (max)</b> | 72.00" (182.9 cm)                             |

### MATERIALS

|             |                    |
|-------------|--------------------|
| <b>Body</b> | Polypropylene      |
| <b>Head</b> | Aluminum           |
| <b>Mast</b> | Aluminum           |
| <b>Lens</b> | Polycarbonate (PC) |

### COLOURS

|   |  |
|---|--|
|  Black |  Yellow |
|---|--|

### LIGHT SPECS

|                       |      |
|-----------------------|------|
| <b>Lumens (High)</b>  | 6000 |
| <b>Lamp Heads</b>     | 1    |
| <b>Lamp Type</b>      | LED  |
| <b>Number of LEDs</b> | 10   |
| <b>Beam Spread</b>    | 125° |
| <b>IP Rating</b>      | 54   |

### POWER

|                         |                        |
|-------------------------|------------------------|
| <b>Run Time (High)</b>  | 3.50 hrs               |
| <b>Run Time (Med)</b>   | 12.00 hrs              |
| <b>Run Time (Low)</b>   | 24.00 hrs              |
| <b>Battery Type</b>     | Sealed Lead Acid (SLA) |
| <b>Rechargeable</b>     | yes                    |
| <b>Battery Lifespan</b> | 500 cycles             |

|                                |  |
|--------------------------------|--|
| <b>Charge Time</b>             | 8 hrs  |
| <b>Battery Level Indicator</b> | Full-time battery level display and low battery warning (visible flashing) |
| <b>Sockets (Primary)</b>       | 1  |
| <b>Volts</b>                   | 12.0v  |


## WEIGHT

|               |                     |
|---------------|---------------------|
| <b>Weight</b> | 32.00 lbs (14.5 kg) |
|---------------|---------------------|

## SWITCH

|                    |                                |
|--------------------|--------------------------------|
| <b>Switch Type</b> | Silicone Rubber Keypad         |
| <b>Light Modes</b> | High / Medium / Low / Flashing |

## ACCESSORIES



**9483**  
Power Supply



**9487**  
Padded Shoulder Strap



**9489**  
Powerpack



**9447**  
DC Vehicle Charger Cord

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 09-11-25*