



3335RZ0

The Peli™ 3335RZ0 is a small & light rechargeable intrinsically safe torch certified for ATEX/UKEX Zone 0 applications.

The 3335RZ0 boasts performance built in providing up to 246 lumens or up to 58 hours of continuous run time, and 3 light modes are provided: High, Low and Flashing. There is a full-time battery level indicator built into the power switch, so you'll always know when it's time to recharge. The Right-Angle Adapter accessory (#3317, sold separately) transforms the torch into a wearable work torch that allows the head to articulate, directing the light exactly where you need it.

- Full Time Battery Level Indication
- 3 modes High / Strobe / Low
- Lanyard (included)
- ATEX Safety Certified Zone 0 (Cat. 1)
- IP67 Rating
- Up to 246 Lumens
- Right-Angle Accessory (#3317, sold separately) transforms the 3335R into hands free wearable flashlight with head rotation capability
- Up to 58 hours run time
- Lithium-Ion rechargeable battery included



DIMENSIONS

| | |
|---------------|-----------------|
| Length | 6.11" (15.5 cm) |
|---------------|-----------------|

MATERIALS

| | |
|---------------|---------------------------------------|
| Body | Anti-static Impact Modified PC/PBT |
| O-Ring | EPDM |
| Lens | Anti-static coated Polycarbonate (PC) |
| Shroud | Anti-static Impact Modified PC/PBT |
| Clip | Stainless Steel |

COLOURS

| |
|--|
|  Yellow |
|--|

LIGHT SPECS

| | |
|------------------|-----|
| Lamp Type | LED |
|------------------|-----|

POWER

| | |
|--------------------------------|-------------|
| Battery Size | 18650 |
| Battery Type | Lithium-Ion |
| Battery Quantity | 1 |
| Batteries Included | yes |
| Rechargeable | yes |
| Charge Time | 12 hrs |
| Battery Level Indicator | RGB LED |
| Volts | 3.7v |

WEIGHT






| | |
|---------------------------------|-----------------|
| Weight With Batteries | 4.6 oz (130 gr) |
| Weight Without Batteries | 3.0 oz (85 gr) |

SWITCH

| | |
|--------------------|-----------------------|
| Switch Type | Push Button |
| Light Modes | High / Low / Flashing |

CERTIFICATIONS

ATEX Zone 0
IECEX ia

| FL1 STANDARD | HIGH | LOW |
|---|---------------|--------------|
|  | 246 LUMENS | 30 LUMENS |
|  | 6h 15mins | 58h 0mins |
|  | 151m | 51m |
|  | 5718cd | 649cd |
|  | IP67 | |

ACCESSORIES



3317
Right Angle Adapter

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 04-16-25