



## BL15135-1321FT

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.



### DIMENSIONS

|                         |  |
|-------------------------|--|
| <b>Interior (L×W×D)</b> | 151.10 x 33.90" x 34.80 (383.8 x 86.1 x 88.4 cm) |
| <b>Exterior (L×W×D)</b> | 155.50 x 38.40" x 42.30 (395 x 97.5 x 107.4 cm)  |
| <b>Lid Depth</b>        | 21.00" (53.3 cm)                                 |
| <b>Bottom Depth</b>     | 13.00" (33 cm)                                   |
| <b>Total Depth</b>      | 34" (86.4 cm)                                    |
| <b>Int Volume</b>       | 103.16 ft <sup>3</sup> (2.921 m <sup>3</sup> )   |

### MATERIALS

|                   |  |
|-------------------|--|
| <b>Body</b>       | RotoMolded Polyethylene  |
| <b>Latch</b>      | Steel (Nickel-black Plated)  |
| <b>O-Ring</b>     | Silicone Sponge  |
| <b>Foam</b>       | No Foam, empty case standard<br>Optional PE and PU, 1 and 2 lb. options filled and lined |
| <b>Purge Body</b> | Aluminum   |
| <b>Handle</b>     | Heavy Duty Injection Molded Standard   |
| <b>Hardware</b>   | Yellow Carbon Steel Standard   |

### COLOURS

### WEIGHT

|               |                       |
|---------------|-----------------------|
| <b>Weight</b> | 297.00 lbs (134.7 kg) |
|---------------|-----------------------|

### TEMPERATURE

|                            |                  |
|----------------------------|------------------|
| <b>Minimum Temperature</b> | -20°F (-28.9 °C) |
| <b>Maximum Temperature</b> | 140°F (60 °C)    |

### OTHER

|                 |     |
|-----------------|-----|
| <b>Military</b> | yes |
|-----------------|-----|

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 07-25-25*