

AL2624-2713AC

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.

• Molded-in, tongue-in-groove gasketed parting lines for splash resistance and tight seals, even after impact

• Reinforced corners and edges for additional impact protection

Molded-in ribs and corrugations for secure, non-slip stacking, columnar

strength, and added protection

Recessed hardware for extra protection

• Positive anti-shear locks, which prevent lid separation after impact, and reduce stress on hardware

• Patented molded-in metal inserts for catch and hinge attachment points,

which provide strength and spread loads to the container

• One-piece construction, molded from lightweight, high-impact polyethylene



DIMENSIONS

Interior (L×W×D)	26.06 x 24.00" x 39.79 (66.2 x 61 x 101.1 cm)	
Exterior (L×W×D)	29.06 x 27.00" x 43.48 (73.8 x 68.6 x 110.4 cm)	
Lid Depth	13.12" (33.3 cm)	
Bottom Depth	26.67" (67.7 cm)	
Total Depth	39.79" (101.1 cm)	
Int Volume	14.4 ft ³ (0.408 m ³)	

MATERIALS

Body	RotoMolded Polyethylene	
Latch	Steel (Nickel-black Plated)	
O-Ring	Silicone Sponge	
Foam	No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined	
Purge Body	Aluminum	
Handle	Heavy Duty Injection Molded Standard	
Hardware	Yellow Carbon Steel Standard	

COLOURS

Gray - 133 Fed Std 26270

WEIGHT

Weight	49.40 lbs (22.4 kg)
Buoyancy	1183.18 lbs (536.7 kg)
Master Pack Weight	51.40 lbs (23.3 kg)

TEMPERATURE

Minimum Temperature -20°F (-28.9 °C)

OTHER

Military

yes

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 07-25-25