

1607

Air

Peli™ Air cases are the first in a series of remarkable innovations engineered by Peli, the pioneers of protective cases. For over 45 years Peli has designed and crafted the most influential protective cases in the world, and we're just getting started.

With the launch of the Peli™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- \bullet Automatic pressure equalization valve balances interior pressure, keeps water out
- Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- · Business card holder
- · Quiet rolling stainless-steel bearing wheels
- Press and Pull™ Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX^{2™} Polymer up to 40% lighter
- · Waterproof O-ring seal
- User-customizable Pick N Pluck[™] foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



CONFIGURATIONS



1607 Standard



1607NF No Foam



1607WDWith Padded Dividers



1607WF With Foam

DIMENSIONS

Interior (L×W×D) 21.05 x 15.81" x 11.63 (53.5 x 40.2 x 29.5 cm) Exterior (L×W×D) 24.13 x 18.80" x 13.25 (61.3 x 47.8 x 33.7 cm)

 Lid Depth
 2.00" (5.1 cm)

 Bottom Depth
 9.60" (24.4 cm)

 Total Depth
 11.6" (29.5 cm)

 Int Volume
 2.24 ft³ (0.063 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Proprietary Polypropylene Blend

Latch ABS
O-Ring EPDM
Purge Body ABS

Purge Vent

Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

Black Orange Silver Yellow

WEIGHT

 Weight With Foam
 16.10 lbs (7.3 kg)

 Weight Empty
 13.20 lbs (6 kg)

 Buoyancy
 178.00 lbs (80.7 kg)

TEMPERATURE

 $\begin{array}{ll} \mbox{Minimum Temperature} & -60\,^{\circ}\mbox{F (-51.1 °C)} \\ \mbox{Maximum Temperature} & 160\,^{\circ}\mbox{F (71.1 °C)} \\ \end{array}$

OTHER

Wheels 2

ACCESSORIES



Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 05-08-24