



iM2300

Storm

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- **Watertight, crushproof, and dustproof**

- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



CONFIGURATIONS



iM2300
Standard



iM2300-X0000
No Foam



iM2300-X0002
With Padded Dividers



iM2300-X0001
With Foam

DIMENSIONS

Interior (L×W×D)	17.00 x 11.70" x 6.20 (43.2 x 29.7 x 15.7 cm)
Exterior (L×W×D)	18.20 x 13.90" x 6.70 (46.2 x 35.3 x 17 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	4.20" (10.7 cm)
Total Depth	6.2" (15.7 cm)
Int Volume	0.71 ft ³ (0.02 m ³)
Padlock Hole Diameter	0.28" (0.7 cm)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

COLOURS

 Black	 OD Green	 Yellow
---	--	--

WEIGHT

Weight With Foam	7.10 lbs (3.2 kg)
Weight Empty	5.90 lbs (2.7 kg)
Buoyancy	45.64 lbs (20.7 kg)
Master Pack Weight	33.00 lbs (15 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)



CERTIFICATIONS

IP67	
------	--

OTHER

Master Pack	4
Military	yes

ACCESSORIES

				
iM2300-LIDORG Lid Organizer	iM2300-FOAM 4 pc. Replacement Foam Set	iM2300-DIV Padded Divider Set	iM-STRAP-S-VER2 Padded Shoulder Strap	iM-LIDSTAY Lid Stay
				
iM2300-M4-BEZEL-L Lid Bezel Kit (Metric)	iM2300-MBEZ-B Base Bezel Kit (Metric)	iM2300-TREK TrekPak Case Divider Kit	1525TPDIV Extra TrekPak Dividers	1506TSA TSA Lock
				
1500D Desiccant Silica Gel				

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 05-16-24