



1650EU

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **4 strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Made in Germany



CONFIGURATIONS



1650EU
Standard



1654
With Padded Dividers



1650NF
No Foam



1650WF
With Foam

DIMENSIONS

| | |
|------------------------------|--|
| Interior (L×W×D) | 28.41 x 17.40" x 10.64 (72.2 x 44.2 x 27 cm) |
| Exterior (L×W×D) | 31.55 x 20.51" x 12.47 (80.1 x 52.1 x 31.7 cm) |
| Lid Depth | 1.81" (4.6 cm) |
| Bottom Depth | 8.84" (22.5 cm) |
| Total Depth | 10.65" (27.1 cm) |
| Int Volume | 3.04 ft³ (0.086 m³) |
| Padlock Hole Diameter | 5/16" (12.7 cm) |

MATERIALS

| | |
|---------------|---------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |

| | |
|-------------------|--------------------------------|
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLOURS

■ Black

WEIGHT

| | |
|-------------------------|----------------------|
| Weight With Foam | 28.06 lbs (12.7 kg) |
| Weight Empty | 24.03 lbs (10.9 kg) |
| Buoyancy | 181.00 lbs (82.1 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41
ATA 300

OTHER

| | |
|--------------------------|-----|
| Wheels | 4 |
| Extendable Handle | yes |
| Master Pack | 1 |
| Nameplate | yes |
| Reduced Area | yes |
| Military | yes |

ACCESSORIES

| | | | | |
|---|---|--|---|---|
|  <p>1651 4 pc. Replacement Foam Set</p> |  <p>1653 Replacement O-ring</p> |  <p>1655 Padded Divider Set</p> |  <p>1659 Photo/Lid Organizer</p> |  <p>1650EUTP TrekPak Case Divider Kit</p> |
|  <p>1507 Quick Mounts - set of 4</p> |  <p>1506TSA TSA Lock</p> |  <p>1500D Desiccant Silica Gel</p> | | |

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 05-20-24