



## iM2275 Storm

Give your gear extra space. With a deeper lid, the iM2275 is the first case in our Peli™ Storm Case™ line that gives you more vertical space to work with for your equipment. This case gives you the freedom to configure multiple 4K cameras, diagnostic circuit readers, or a drone with accessories.

- **Watertight, crushproof, and dustproof**

- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



### CONFIGURATIONS



**iM2275**  
Standard



**iM2275-X0000**  
No Foam



**iM2275-X0006**  
With TrekPak Divider System



**iM2275-X0001**  
With Foam

### DIMENSIONS

<b>Interior (LxWxD)</b>	14.12 x 13.19" x 9.90 (35.9 x 33.5 x 25.1 cm)
<b>Exterior (LxWxD)</b>	15.25 x 15.50" x 10.22 (38.7 x 39.4 x 26 cm)
<b>Lid Depth</b>	3.20" (8.1 cm)
<b>Bottom Depth</b>	6.30" (16 cm)
<b>Total Depth</b>	9.5" (24.1 cm)
<b>Int Volume</b>	1.07 ft <sup>3</sup> (0.03 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.37" (0.9 cm)

### MATERIALS

<b>Body</b>	Injection Molded HPX™ high performance resin
<b>Latch</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Latch (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>O-Ring</b>	EPDM
<b>Pins</b>	Stainless Steel
<b>Pins (Alt)</b>	Aluminum
<b>Foam</b>	1.3/1.35 polyester
<b>Purge Body</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Purge Body (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>Purge Vent</b>	Gortex membrane

## COLOURS

---

■ Black

## WEIGHT

---

**Weight With Foam** 10.25 lbs (4.6 kg)  
**Weight Empty** 8.00 lbs (3.6 kg)  
**Buoyancy** 68.80 lbs (31.2 kg)

## TEMPERATURE

---

**Minimum Temperature** -20°F (-28.9 °C)  
**Maximum Temperature** 140°F (60 °C)

## CERTIFICATIONS

---

**IP67**

## OTHER

---

**Master Pack** 3  
**Military** yes

## ACCESSORIES

---



**iM-STRAP-S-VER2**  
Padded Shoulder Strap



**iM-LIDSTAY**  
Lid Stay



**iM2275-FOAM**  
4 pc. Replacement Foam Set



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 02-04-25