



472-PWC-DW3200

Mobile Armory™

FieldPak

The FieldPak from Peli-Hardigg™ combines a softshell padded rifle case with our toughest hardshell protective case for the best of both worlds. In the field, the softshell padded case is lightweight and maneuverable enough to get you into position quickly. On the move, the padlockable hardshell case backs it up with impact, temperature, and moisture resistance for total protection. Together, they offer the most security possible for your weapon. Don't go halfway when it comes to protecting your weapon - go double duty.

Holds two 472-DW3200 soft rifle bags and up to 4 rifles.

- Six Press & Pull Latches
- Two Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- In-line Wheels
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX™ Resin
- Watertight
- Peli's limited lifetime guarantee*
- *Where applicable by law



CONFIGURATIONS




472-PWC-DW3200
Standard




472-PWC-DW3200-BLK-BLK
Black Case With Black Soft Case



472-PWC-DW3200-BLK-COY
Black Case With Coyote Soft Case



472-PWC-DW3200-OD-BLK
Green Case With Black Soft Case



472-PWC-DW3200-OD-COY
Green Case With Coyote Soft Case

DIMENSIONS

Interior (L×W×D)	44.00 x 14.00" x 6.00 (111.8 x 35.6 x 15.2 cm)
Exterior (L×W×D)	47.20 x 16.50" x 6.70 (119.9 x 41.9 x 17 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	4.00" (10.2 cm)
Total Depth	6" (15.2 cm)
Int Volume	2.14 ft³ (0.061 m³)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	Silicone Sponge
Pins	Stainless Steel
Foam	1.3/1.35 polyester

Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

COLOURS

 Black	 OD Green
---	--

WEIGHT

Weight	21.10 lbs (9.6 kg)
---------------	--------------------

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

OTHER

Wheels	2
---------------	---

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 05-19-24