

# 0370 Protector Cube Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli<sup>™</sup> Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

### • Large 2-person fold down handles

- Watertight, crushproof, and dustproof
- 3 level Pick N Pluck  $^{\rm m}$  with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps
- water out • O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



# CONFIGURATIONS



0370 Standard



0374 With Padded Dividers



**0370NF** No Foam



0370WF With Foam

## DIMENSIONS

Interior (L×W×D)	24.00 x 24.00" x 24.00 (61 x 61 x 61 cm)
Exterior (L×W×D)	26.50 x 26.50" x 25.25 (67.3 x 67.3 x 64.1 cm)
Lid Depth	5.00" (12.7 cm)
Bottom Depth	19.00" (48.3 cm)
Total Depth	24" (61 cm)
Int Volume	8 ft <sup>3</sup> (0.227 m <sup>3</sup> )
Padlock Hole Diameter	0.31" (0.8 cm)

### MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS

#### Purge Vent

### COLOURS

Black

### WEIGHT

Weight With Foam	41.00 lbs (18.6 kg)
Weight Empty	31.97 lbs (14.5 kg)
Buoyancy	465.18 lbs (211 kg)
Master Pack Weight	46.78 lbs (21.2 kg)

### TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

### CERTIFICATIONS

IP67 Def Stan 81-41

### OTHER

## ACCESSORIES





**0357** Cube Case Mobility Package 0371 8 pc. Replacement Foam Set



1507 Quick Mounts - set of 4



1506TSA

TSA Lock





0373 Replacement O-ring



1500D Desiccant Silica Gel



0375 Padded Divider Set



**0379** Lid Organizer

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 05-09-24