



1400EU Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived. These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel padlock protectors
- Made in Germany



CONFIGURATIONS



1400EU
Standard



1400WF
With Foam

DIMENSIONS

Interior (L×W×D)	11.87 x 8.97" x 5.15 (30.1 x 22.8 x 13.1 cm)
Exterior (L×W×D)	13.68 x 11.61" x 5.75 (34.7 x 29.5 x 14.6 cm)
Lid Depth	1.18" (3 cm)
Bottom Depth	4.00" (10.2 cm)
Total Depth	5.18" (13.2 cm)
Int Volume	0.32 ft³ (0.009 m³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

 Black	 Desert Tan	 Orange	 OD Green
 Silver	 Yellow		

WEIGHT

Weight With Foam	4.41 lbs (2 kg)
Weight Empty	3.97 lbs (1.8 kg)
Buoyancy	20.06 lbs (9.1 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41

OTHER

Master Pack	4
Nameplate	yes
Military	yes

ACCESSORIES

				
1401 3 pc. Replacement Foam Set	1403 Replacement O-ring	1400PF Special Application Panel Frame	1506TSA TSA Lock	1500D Desiccant Silica Gel

Peli
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 05-20-24