

1520EU Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

• Watertight, crushproof, and dustproof

Automatic pressure equalization valve - balances interior pressure, keeps water out

- Comfortable rubber over-molded handle
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck[™] with convoluted lid foam
- Stainless steel hardware and padlock protectors
- Made in Germany
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1520EU Standard



1524 With Padded Dividers



1520NF No Foam



1520WF With Foam

DIMENSIONS

| Interior (L×W×D) | 17.68 x 12.53" x 6.73 (44.9 x 31.8 x 17.1 cm) |
|-----------------------|---|
| Exterior (L×W×D) | 19.65 x 15.49" x 7.53 (49.9 x 39.3 x 19.1 cm) |
| Lid Depth | 1.79" (4.5 cm) |
| Bottom Depth | 4.93" (12.5 cm) |
| Total Depth | 6.72" (17.1 cm) |
| Int Volume | 0.86 ft ³ (0.024 m ³) |
| Padlock Hole Diameter | 5/16" (12.7 cm) |

MATERIALS

| Body | Polypropylene |
|--------|---------------------|
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |

Purge BodyABSPurge Vent3 Micron Hydrophobic Non-Woven

COLOURS

| Black | Desert Tan | Orange | OD Green |
|--------|------------|--------|----------|
| Silver | Yellow | | |

WEIGHT

| Weight With Foam | 9.35 lbs (4.2 kg) |
|--------------------|---------------------|
| Weight Empty | 8.29 lbs (3.8 kg) |
| Buoyancy | 63.00 lbs (28.6 kg) |
| Master Pack Weight | 23.30 lbs (10.6 kg) |

TEMPERATURE

| Minimum Temperature | -40°F (-40 °C) |
|---------------------|-----------------|
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

| IP67 |
|----------------|
| MIL C-4150J |
| Def Stan 81-41 |

OTHER

| Master Pack | 2 |
|-------------|-----|
| Nameplate | yes |
| Military | yes |

ACCESSORIES



1508 Photographer's Lid Organizer



1520TPKIT TrekPak Case Divider Kit



1509 Lid Organizer



1507 Quick Mounts - set of 4



1521 3 pc. Replacement Foam Set



1506TSA TSA Lock



1523 Replacement O-ring



1500D Desiccant Silica Gel



1525 Padded Divider Set



1520PF Special Application Panel Frame



1520TPDIV Extra TrekPak Dividers

> Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

> > Document created on 05-12-24